

FIXOLITE CLASSIC (CL blocks)**Reference : B-CL25/18**

Fixolite wall blocks, made in Belgium

. Dimensions are 50 cm wide, 25 cm high (1m² = 8 blocks) and depth varies according to requirements. The block is made of wood-cement and, as an option, fire-retardant expanded polystyrene insulation (density 40 gr/m³).

Total thickness	25.0 cm
-----------------	---------

Insulation thickness	0.0 cm
----------------------	--------

Concrete thickness	18.0 cm
--------------------	---------

Interior side thickness	3.5 cm
-------------------------	--------

Exterior side thickness	3.5 cm
-------------------------	--------

Concrete volume	130.0 l/m ²
-----------------	------------------------

Density	± 510 kg/m ³
---------	-------------------------

Weight	53.92 kg/m ²
--------	-------------------------

Thermal insulation λ	0.10 W/m ² K
----------------------	-------------------------

R coefficient	1.25 m ² K/W
---------------	-------------------------

U coefficient	0.8 W/m ² K
---------------	------------------------

Sound absorption α	> 90% (100→5000Hz)
--------------------	--------------------


Sound insulation	54 dB
------------------	-------

Reaction to fire	Non-flammable (M1)
------------------	--------------------

Fire resistance	> 6h (ISO 834)
-----------------	----------------


Rot-proof	✓
-----------	---

Flexural strength	± 200 DaN
-------------------	-----------

**Fixolite classic block range**

Fixolite offers 5 classic block sizes.



30 and 36 cm blocks are available with internal insulation.

**Notes**

Block for load-bearing walls (without polystyrene).

Special block:

- "D" to be cut in 2



English version :

https://fixolite.eu/doc/B_CL25_18.en.pdf



Version française :

https://fixolite.eu/doc/B_CL25_18.fr.pdf